



F/V

LOADING TABLE

Tanks	A 23,711 gal	B 19,587 gal	C 15,146 gal	D 7,312 gal	E 2,457 gal
F01.P/S	98%	98%	0%	0%	0%
F02.P/S	98%	98%	98%	0%	0%
F03.P/S	98%	98%	98%	98%	30%
F04.C	98%	0%	0%	0%	0%
FODAY.S	98%	ANY LEVEL	ANY LEVEL	ANY LEVEL	ANY LEVEL
Hold Condition	A to B	B to C	C to D	D to E	
All Holds Empty (FWBALL.C any level)	Tier 1	71	71	71	71
	Tier 2	27	27	27	27
	Tier 3	27	27	27	27
	Tier 4	22	27	27	27
	Total	147	152	152	152
Forward Hold Full (Aft Empty) (FWBALL.C any level)	Tier 1	71	71	71	71
	Tier 2	27	27	27	27
	Tier 3	27	27	27	27
	Tier 4	6	27	27	27
	Total	131	152	152	152
All Holds Full (FWBALL.C empty)	Tier 1	41	71	71	71
	Tier 2	0	12	27	27
	Tier 3	0	0	24	27
	Tier 4	0	0	0	20
	Total	41	83	122	145
	(see Note 4)	(see Note 4)	(see Note 4)	(see Note 4)	

Notes:

1. This Loading Table is subject to the restrictions listed in the attached "Operating Instructions".
2. Rectangular pots were assumed to measure 7'-0" X 7'-0" X 34" X 725 lbs each, including lines & buoys.
3. The gallorage for each fuel condition includes fuel in the day tank.
4. Conditions referencing this note may have less than 6" of freeboard, depending on consumables loading. Loads should be reduced to maintain 6" of freeboard.
5. Under icing conditions, reduce the pot load by 45 pots from the uppermost tiers. Do not operate where this reduction results in a negative pot load.