



Naval Facilities Engineering Systems Command Southwest  
BRAC PMO West  
San Diego, CA

## **Air Monitoring Summary Report**

**January 1 to January 31, 2022**

Phase IV Non-Time Critical Removal Action, Solid Waste  
Disposal Area Westside, Installation Restoration Site 12  
Former Naval Station Treasure Island  
San Francisco, CA  
April 2022



Naval Facilities Engineering Systems Command Southwest  
BRAC PMO West  
San Diego, CA

## **Air Monitoring Summary Report January 1 to January 31, 2022**

Phase IV Non-Time Critical Removal Action, Solid Waste  
Disposal Area Westside, Installation Restoration Site 12  
Former Naval Station Treasure Island  
San Francisco, CA  
April 2022

DCN: GLBN-0005-F5271-0021

### **Prepared for:**

Department of the Navy  
Naval Facilities Engineering Systems Command Southwest  
BRAC PMO West  
33000 Nixie Way, Bldg. 50  
San Diego, CA 92147

### **Prepared by:**



Gilbane Federal  
1655 Grant Street, Suite 1200  
Concord, California 94520  
Contract Number: N62473-17-D-0005; Task Order No. N62473-18-F5271

---

## Table of Contents

1.0	Introduction .....	1-1
2.0	Monitoring Site Locations .....	2-1
2.1	Dust Monitoring.....	2-1
2.2	Air Monitoring.....	2-1
2.3	Radiological Air Monitoring .....	2-2
3.0	Sampling and Analytical Methods.....	3-1
3.1	Dust Samples .....	3-1
3.2	Air Samples .....	3-1
3.3	Radiological Air Samples.....	3-2
4.0	Dust Monitoring Results.....	4-1
5.0	Air Monitoring Results.....	5-1
6.0	References .....	6-1

## List of Figures

Figure 1	Air and Dust Monitoring Locations IR Site 12 SWDA Westside
Figure 2	Wind Rose IR Site 12 SWDA Westside

## List of Tables

Table 1	Dust Monitoring Project Action Levels
Table 2	Air Monitoring Project Screening Criteria

## List of Attachments

Attachment 1	PDR Summary Table and Field Forms
Attachment 2	Summary of Air Monitoring and Air Sampling Results
Attachment 3	Radiological Air Monitoring Results

## Acronyms and Abbreviations

AMP	Air Monitoring Plan
BAAQMD	Bay Area Air Quality Management District
BAP(Eq)	benzo(a)pyrene equivalency
cfm	cubic feet per minute
CFR	Code of Federal Regulations
DAC	derived air concentration
DCP	Dust Control Plan
DTSC	Department of Toxic Substances Control
Gilbane	Gilbane Federal
HERO	Human and Ecological Risk Office
IR	Installation Restoration
mg/m <sup>3</sup>	milligram per cubic meter
Navy	U.S. Department of the Navy
PAH	polycyclic aromatic hydrocarbon
PCB	polychlorinated biphenyl
PDR	personal data-logging real-time aerosol monitor
PM10	particulate matter less than 10 microns in diameter
PUF	polyurethane foam
Ra-226	radium-226
TCDD	2,3,7,8-tetrachlorodibenzo-p-dioxin
TLV	threshold limit value
TSP	total suspended particulates
µg/m <sup>3</sup>	microgram per cubic meter
USEPA	United States Environmental Protection Agency
Work Plan	<i>Final Work Plan, Phase IV Non-Time Critical Removal Action, Solid Waste Disposal Area Westside, Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California</i>

## 1.0 Introduction

This Air Monitoring Report was prepared by Gilbane Federal (Gilbane) as requested by the United States Department of the Navy (Navy) under the Radiological Multiple Award Contract (RADMAC II) N62473-12-D-D005, Contract Task Order N6247317F5271. Gilbane is performing dust and air monitoring at Former Naval Station Treasure Island in accordance with the Final Dust Control Plan (DCP) and Air Monitoring Plan (AMP), included as appendices to *Phase IV Non-Time Critical Removal Action Work Plan, Solid Waste Disposal Area Westside, Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California* (Work Plan; Gilbane, 2021).

The DCP describes best management practices and procedures to be implemented to minimize dust generation during work activities. Dust monitoring is conducted to ensure that these procedures are effective. Dust monitoring is also conducted to verify that the working environment meets occupational health and safety standards and that workers are safe. The AMP outlines the requirements for prevention of exposure for construction workers to dust and potential airborne chemicals of concern from the work area. The AMP also establishes the conservative project action levels for dust at the work area boundary to protect residents.

This summary report describes the following:

- Dust and air monitoring sampling locations – **Section 2.0**,
- Dust and air monitoring sample collection and analytical methods – **Section 3.0**,
- Dust and air monitoring data – **Section 4.0**, and,
- Dust and air monitoring results – **Section 5.0**.

This summary report presents the dust and air monitoring test results at Installation Restoration (IR) Site 12 from January 1<sup>st</sup> through January 31<sup>st</sup>, 2022 and compares the results with the established action levels included in the Work Plan (Gilbane, 2021). During this reporting period, the Site 12 air monitoring stations (AMSW1 and AMSW2) operated on January, 24<sup>th</sup>, 25<sup>th</sup>, 26<sup>th</sup>, 27<sup>th</sup>, and 28<sup>th</sup> for earth-moving tasks involving potentially contaminated soil. The air monitoring stations were shut down for the remainder of the month as operationally the crew was receiving clean import backfill soil and not performing earth-moving tasks involving potentially contaminated soil. Dust monitoring using the PDR stations continued through the duration of the month while the field team acquired clean import soil and began grading.

During the reporting period, personal data-logging real-time aerosol monitoring (PDR) dust data was collected. Air samples were collected and analyzed for lead, polychlorinated biphenyls (PCBs), polycyclic aromatic hydrocarbons (PAHs), dioxin [2,3,7,8-tetrachlorodibenzo-p-dioxin (TCDD)], total suspended particulates (TSP), and particulate matter less than 10 microns in diameter (PM10). In addition, air samples were analyzed for radiological gross alpha and beta levels.

This page intentionally left blank

## 2.0 Monitoring Site Locations

### 2.1 Dust Monitoring

During earthmoving activities, several PDR stations are set up to monitor real-time airborne dust concentrations. The purpose of the PDR stations is to act as a first line of defense in protecting workers' health, and ultimately the public's health, during field activities. PDR stations are situated immediately adjacent to the current work area locations most likely to generate the greatest volume of airborne dust and are adjusted as necessary due to changes in wind direction and/or work location. Real-time dust monitoring ensures dust levels remain below action levels during fieldwork operations.

The general locations for dust monitors in IR Site 12 are shown on **Figure 1**. Specific locations of each PDR are described in the individual PDR daily data files. Field forms from each location are presented in **Attachment 1** of this report. During earth moving activities at IR Site 12 (i.e., transportation of excavated soil to the radiological screening yard, excavation, and backfilling), one PDR serves as the upwind (background) location (DMW19, DMW22, DMW25) and two PDRs are placed in downwind perimeter locations (DMW20, DMW21, DMW23, DMW24, DMW26, DMW27).

### 2.2 Air Monitoring

Air monitoring samples collected using high volume samplers are collected to identify and quantify airborne contaminants and to confirm the results recorded during dust (PDR) monitoring. Air monitoring stations are mobilized to collect air monitoring samples upwind and downwind of work areas. General locations of the IR Site 12 air monitoring stations are shown on **Figure 1**. The locations of the air monitoring stations are determined based on the prevailing wind direction (typically from the southwest) and are modified as needed.

Weather forecasts including wind direction are checked daily with a weather station located at Building 572. The weather station records temperature, pressure, wind speed and direction, etc., every 30 minutes, 24 hours per day. Wind speed is also monitored near the work site during soil excavation and handling to ensure that work is stopped if sustained winds over 25 miles per hour are encountered. No work stoppages due to sustained wind speed exceedances were required during this reporting period. Wind speed and direction data gathered during work hours for this reporting period, presented on a wind rose diagram in **Figure 2**, generally depict the wind blowing between the South and West directions at 3-6 miles/hour with gusts up to 12 miles/hour. Detailed weather data is not reported in this document but can be provided upon request.

High volume air monitoring stations remain stationary while sampling is being conducted; however, locations may be adjusted when the wind direction changes and

when overall excavation work areas change from one site to another. Each upwind and downwind high-volume monitoring station includes separate monitoring systems for the following:

- TSP - collected daily
- PM10 - collected daily
- Lead - collected daily
- PAHs, PCBs, and dioxin - collected on alternating days

## **2.3 Radiological Air Monitoring**

Radiological air samplers are positioned adjacent to excavation work activities for radiologically impacted soil at one upwind and one downwind location during earthmoving activities associated with radiologically impacted soil. The radiological air samplers may be co-located with PDRs or the high-volume samplers.



## **3.0 Sampling and Analytical Methods**

Dust and air samples are collected during earthmoving activities. However, during precipitation events, the dust and air monitoring units may not be operable. An attempt will be made to collect samples and readings regardless of the weather. If dust or air monitors are found to be malfunctioning or nonfunctional, earthmoving activities will stop until monitors can be repaired or replaced. The Site Health and Safety Officer is responsible for monitoring the air and dust monitoring sampling equipment. In rare cases, due to ancillary equipment malfunction such as generator failure during the night, a sample may be collected that represents a period of less than 24 hours. If this situation occurs, a note is added to the sample result data tables indicating why the full sampling period was not achieved. All AMS samplers run approximately 24 hours before the sample is collected however per FCR04 the final set of samples for the week will be collected on the last workday of the week once intrusive activities have finished for the day. These samples will have a runtime of 8-10 hours to cover the full work shift which meets the minimum 4-hour runtime required for lab analysis. Two sets of samples will be sent to the lab for examination on that final workday of the week. The results will be adjusted for the reduced runtime and fully comparable against project screening criteria.

### **3.1 Dust Samples**

The PDR is a high sensitivity photometric monitor with a light-scattering sensing configuration that has been optimized for the measurement of the respirable fraction of airborne dust, smoke, fumes, and mists. PDRs are used to evaluate real-time monitoring of airborne dust concentrations, to determine if there is a need for additional dust control or personal protection.

### **3.2 Air Samples**

Air samples were sampled in accordance with the United States Environmental Protection Agency (USEPA) reference sampling method for PM<sub>10</sub>, described in 40 Code of Federal Regulations (CFR) 50, Subpart J. Each sample was collected on a filter over an approximately 24-hour period; the filter was then weighed to determine the amount of PM<sub>10</sub> collected.

TSP samples were collected with a high-volume (39 to 60 cubic feet per minute [cfm]) air sampler in accordance with USEPA's reference sampling method for TSP, described in Title 40 CFR, Part 50, Subpart B. Each sample was collected on a filter over an approximately 24-hour period; the filter was then weighed to determine the amount of TSP collected. Once the filter weight was determined, the sample was analyzed for lead in accordance with USEPA Method 6020 using inductively coupled mass spectrometry.

Air samples for PCBs, PAHs, and dioxin are collected and analyzed in accordance

with USEPA Methods TO-4A, TO-13, TO-9A, respectively, using TISCH polyurethane (PUF) samplers. The filter media collected from the air samplers is submitted to the analytical laboratory for appropriate analysis.

PCB, PAH, and dioxin samples are collected on alternating days at the downwind and upwind stations during earthmoving activities.

### **3.3 Radiological Air Samples**

Radiological air monitoring is also conducted upwind and downwind on days of earthmoving activities. Radiological samples are collected with a LV-1 low volume air sampler. Air filters are counted on site following a decay period and are compared with public air concentration limits published in 10 CFR Part 20. Radiological air sampling methods and procedures are detailed in Gilbane Radiological Procedure PR-RP-150 *Radiological Survey and Sampling* (Gilbane, 2016).

The radiological air sample is counted on a Low Background Protean WPC-9950 and analyzed for gross alpha and beta activity. The calculated airborne concentration in microcuries is then compared to the effluent concentration (often but incorrectly refer to as a derived air concentration [DAC] which applies only to occupational exposures) limit specified in Table 2 of Appendix B to 10 CFR 20. The effluent concentration is the concentration of a given radionuclide in air which, if inhaled continuously over the course of a year, results in an exposure equal to the annual regulatory limit specified in 10 CFR 20.1302. The threshold for radiological effluent air monitoring samples is 10 percent of the effluent concentration, which ensures work practices are evaluated and modified as necessary to ensure the limit is not reached.

## 4.0 Dust Monitoring Results

If dust (PDR) monitoring equipment alarms, the source of exceedance will be determined by evaluating both upwind and downwind dust (PDR) sample locations. If the difference between upwind and downwind concentrations is greater than the action level for a sustained period of 15 minutes, then earthmoving activities will be halted until dust control measures are implemented. These may include, but are not limited to, adding water to the work area during earth moving tasks, evaluation of alternate work procedures or equipment, and/or cessation of the activity that is creating the dust until the PDR readings are below the screening criteria.

Dust monitoring action levels that are implemented on a real-time basis are listed in **Table 1**. PDR data are collected and reviewed each day by the Site Health and Safety Manager. PDR data are included in **Attachment 1**.

On January 6<sup>th</sup>, 10<sup>th</sup>, 12<sup>th</sup>, 13<sup>th</sup>, 17<sup>th</sup>, 19<sup>th</sup>, 20<sup>th</sup>, 24<sup>th</sup>, 25<sup>th</sup>, 26<sup>th</sup>, 27<sup>th</sup>, 28<sup>th</sup>, and 31<sup>st</sup> PDR readings were observed above project screening criteria, however, the delta between the upwind and downwind monitors remained below action levels. On these days the field team documented foggy, hazy, and or thick low hanging marine layer conditions presented in **Attachment 1**. On the days mentioned above, elevated or high readings were noted during setup before any intrusive activities had begun. In conclusion, field work continued as field activities were not generating visible dust and onsite atmospheric conditions generated elevated PDR data.

**Table 1: Dust Monitoring Project Action Levels**

Method	Monitoring Location	Monitoring Frequency <sup>a</sup>	Action Level <sup>b</sup>	Action
PDR	Near Workers' Breathing Zones (typically on equipment)	Periodically <sup>c</sup>	<2.0 mg/m <sup>3</sup> >2.0 mg/m <sup>3</sup>	<2.0 mg/m <sup>3</sup> continue work in Level D. Increase dust control (i.e., apply water or other suppression method) and/or upgrade to Level C if concentrations >2.0 mg/m <sup>3</sup> .
	Job Site Perimeter	Continuously	<1.0 mg/m <sup>3</sup> >1.0 mg/m <sup>3</sup>	Continue work. STOP work, apply water or other dust suppression methods until levels decrease below 1.0 mg/m <sup>3</sup>

**Notes:**

Only the Health and Safety Manager is authorized to downgrade levels of personal protective equipment.

- <sup>a</sup> Frequency of air monitoring may be adjusted by the project Certified Industrial Hygienist after sufficient characterization of site contaminants has been completed, tasks have been modified, or site controls have proven effective.
- <sup>b</sup> Five readings exceeding the action level in any 15-minute period or a sustained reading exceeding the action level for five minutes will trigger a response. Action levels represent airborne particulate concentrations in excess of background particulate concentrations.
- <sup>c</sup> PDR will be monitored a minimum of three times a day.
- < less than
- > greater than
- mg/m<sup>3</sup> milligrams per cubic meter
- PDR personal data-logging real-time aerosol monitor

**Table 2: Air Monitoring Project Screening Criteria**

<b>Chemicals of Concern</b>	<b>Project Screening Criteria (Threshold Limit Value) <math>\mu\text{g}/\text{m}^3</math></b>	<b>Basis</b>
Lead	1,575	TI Site 12 Subchronic Dust Action Level
TSP	50	TI Site 12 Dust Action Level
PM10	50	BAAQMD Ambient Air Quality Standard
BAP(Eq)	55,330	TI Site 12 Chronic Dust Action Level
PCBs <sup>a</sup>	NA	TI Site 12 Dust Action Level
Dioxin <sup>a</sup>	1E+07	TI Site 12 Chronic Dust Action Level
Radiological (Ra-226)	10% of DAC <sup>c</sup>	Occupational and public air concentration limits for Ra-226 published in 10 Code of Federal Regulations Part 20.

**Notes:**

- <sup>a</sup> The dust action level was increased by a factor of 10 to account for the short-term duration of the project relative to the lifetime assumptions incorporated into the toxicity criteria and exposure assumption.
- <sup>b</sup> BAP(Eq) action level will be  $\sim 55 \text{ mg}/\text{m}^3$  for all excavations
- <sup>c</sup> Public air concentration limits are commonly referred to as DAC, but are actually Effluent Concentrations from Table 2 for 10 CFR Part 20.

BAAQMD	Bay Area Air Quality Management District
BAP(Eq)	benzo(a)pyrene equivalency
DAC	derived air concentration
$\text{mg}/\text{m}^3$	milligrams per cubic meter
PCBs	polychlorinated biphenyls
PM10	particulate matter smaller than 10 microns in diameter
Ra-226	radium-226
TSP	total suspended particulates
$\mu\text{g}/\text{m}^3$	micrograms per cubic meter

This page intentionally left blank

## 5.0 Air Monitoring Results

The Human and Ecological Risk Office (HERO) at the request of the California Department of Toxic Substances Control (DTSC) developed dust action levels for community air monitoring for IR Site 12. Sub-chronic and chronic dust action levels as PM10 were calculated for lead, dioxin, benzo(a)pyrene (BAP) equivalency (Eq) by PAHs analysis, and PCBs. As presented in the document *Dust Action Levels for Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California* (HERO, 2018), the action levels were calculated using the maximum chemicals of concern soil concentrations at IR Site 12.

Based on HERO's recommendations, a PM10 dust action level of 50 microgram per cubic meter ( $\mu\text{g}/\text{m}^3$ ) will be implemented for all excavation areas at IR Site 12. TSP is expected to be further controlled based on the limit employed for PM10, in accordance with guidance provided by the San Francisco Bay Area Air Quality Management District (BAAQMD), which estimates that PM10 makes up approximately 55 percent of TSP. If it is apparent that project activities are the cause of exceedances, additional control measures will be considered and implemented.

Analytical results from air monitoring samples are compared with the project screening criteria (threshold limit values [TLV]) listed in **Table 2**. Air monitoring results are included in **Attachment 2**. Weather information (including ambient pressure and temperature data) and high-volume air monitoring sample results are presented in **Attachment 2**. Weather information was collected from the weather station at Building 572, Avenue M, Treasure Island, San Francisco, California. Radiological air monitoring results are presented in **Attachment 3**.

PM10 analytical results from January 2022 did not exceed the project-specific screening criteria presented in **Table 2-2**.

TSP analytical results from January 2022 did not exceed project-specific screening criteria presented in **Table 2-3**.

Metals (lead), PAHs, total PCBs, and dioxin analytical results from January 2022, did not exceed the project-specific screening criteria presented in **Table 2-4** through **Table 2-7**.

On January 25<sup>th</sup>, 2022 the field team documented a generator malfunction at the upwind AMSW2 air sampler. The downwind generator turned off after business hours due to an undetermined origin shutting off the AMS stations overnight. The generator was turned back on when field personnel arrived onsite the next morning and the stations operated according to design. The sample media runtime ran greater than the four-hour minimum so the samples were sent for analysis. The lab results were adjusted for the smaller runtime which makes the data representative.

This page intentionally left blank




## 6.0 References


- Gilbane, 2016. *Radiological Procedure PR-RP-150 Radiological Survey and Sampling*. January.
- Gilbane, 2021. *Phase IV Non-Time Critical Removal Action Work Plan, Solid Waste Disposal Area Westside, Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California*. March.
- Gilbane, 2021. *Phase IV Non-Time Critical Removal Action Work Plan, Air Monitoring Plan, Solid Waste Disposal Area Westside, Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California*. March.
- Gilbane, 2021. *Phase IV Non-Time Critical Removal Action Work Plan, Dust Control Plan, Solid Waste Disposal Area Westside, Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California*. March.
- HERO, 2018. *Dust Action Levels for Installation Restoration Site 12, Former Naval Station Treasure Island, San Francisco, California*. September.

This page intentionally left blank

## FIGURES

This page intentionally left blank





**ATTACHMENT 1**  
**PDR SUMMARY TABLE AND FIELD FORMS**  
**(Provided on CD)**

This page intentionally left blank



Table 1-1: Personal Data-Logging Real-Time (PDR) Aerosol Monitoring Results

DustTrak Unit	IR Site	Date	Maximum <sup>1</sup> (mg/m <sup>3</sup> )	Average <sup>1</sup> (mg/m <sup>3</sup> )	Delta Between Upwind and Downwind Stations (mg/m <sup>3</sup> )	Below action level? (0.050 mg/m <sup>3</sup> ) (Yes/No)
DMW19	Site 12	1/3/2022	0.033	0.010	NA	Yes
DMW20	Site 12		0.029	0.017	0.007	Yes
DMW21	Site 12		0.025	0.009	-0.001	Yes
DMW19	Site 12	1/4/2022	0.016	0.012	NA	Yes
DMW20	Site 12		0.018	0.013	0.001	Yes
DMW21	Site 12		0.016	0.012	0.000	Yes
DMW19	Site 12	1/5/2022	0.032	0.015	NA	Yes
DMW20	Site 12		0.029	0.016	0.001	Yes
DMW21	Site 12		0.027	0.015	0.000	Yes
DMW19	Site 12	1/6/2022	<b>0.055</b>	0.036	NA	Yes
DMW20	Site 12		<b>0.063</b>	0.042	0.006	Yes
DMW21	Site 12		<b>0.052</b>	0.034	-0.002	Yes
DMW19	Site 12	1/7/2022	0.019	0.012	NA	Yes
DMW20	Site 12		0.017	0.009	-0.003	Yes
DMW21	Site 12		0.015	0.007	-0.005	Yes
DMW19	Site 12	1/10/2022	<b>0.053</b>	0.024	NA	Yes
DMW20	Site 12		<b>0.070</b>	0.030	0.006	Yes
DMW21	Site 12		<b>0.064</b>	0.033	0.009	Yes
DMW19	Site 12	1/11/2022	0.043	0.029	NA	Yes
DMW20	Site 12		0.049	0.036	0.007	Yes
DMW21	Site 12		0.048	0.032	0.003	Yes
DMW19	Site 12	1/12/2022	<b>0.094</b>	0.078	NA	Yes
DMW20	Site 12		<b>0.122</b>	0.092	0.014	Yes
DMW21	Site 12		<b>0.103</b>	0.092	0.014	Yes
DMW19	Site 12	1/13/2022	<b>0.124</b>	0.094	NA	Yes
DMW20	Site 12		<b>0.146</b>	0.117	0.023	Yes
DMW21	Site 12		<b>0.129</b>	0.103	0.009	Yes
DMW19	Site 12	1/14/2022	0.020	0.017	NA	Yes
DMW20	Site 12		0.023	0.019	0.002	Yes
DMW21	Site 12		0.033	0.023	0.006	Yes
DMW19	Site 12	1/17/2022	<b>0.057</b>	0.030	NA	Yes
DMW20	Site 12		<b>0.057</b>	0.032	0.002	Yes
DMW21	Site 12		<b>0.069</b>	0.036	0.006	Yes
DMW19	Site 12	1/18/2022	0.032	0.020	NA	Yes
DMW20	Site 12		0.035	0.021	0.001	Yes
DMW21	Site 12		0.039	0.022	0.002	Yes
DMW19	Site 12	1/19/2022	<b>0.085</b>	0.055	NA	Yes
DMW20	Site 12		<b>0.089</b>	0.060	0.005	Yes
DMW21	Site 12		<b>0.094</b>	0.059	0.004	Yes
DMW19	Site 12	1/20/2022	<b>0.052</b>	0.038	NA	Yes
DMW20	Site 12		<b>0.057</b>	0.043	0.005	Yes
DMW21	Site 12		<b>0.065</b>	0.044	0.006	Yes
DMW19	Site 12	1/24/2022	<b>0.057</b>	0.011	NA	Yes
DMW20	Site 12		<b>0.060</b>	0.009	-0.002	Yes
DMW21	Site 12		<b>0.060</b>	0.012	0.001	Yes
DMW22	Site 12	1/25/2022	<b>0.101</b>	0.050	NA	Yes
DMW23	Site 12		<b>0.109</b>	0.057	0.007	Yes
DMW24	Site 12		<b>0.108</b>	0.058	0.008	Yes
DMW22	Site 12	1/26/2022	<b>0.092</b>	0.072	NA	Yes
DMW23	Site 12		<b>0.092</b>	0.078	0.006	Yes
DMW24	Site 12		<b>0.107</b>	0.086	0.014	Yes
DMW22	Site 12	1/27/2022	<b>0.090</b>	0.062	NA	Yes
DMW23	Site 12		<b>0.097</b>	0.062	0.000	Yes
DMW24	Site 12		<b>0.100</b>	0.073	0.011	Yes
DMW22	Site 12	1/28/2022	<b>0.072</b>	0.052	NA	Yes
DMW23	Site 12		<b>0.063</b>	0.054	0.002	Yes
DMW24	Site 12		<b>0.067</b>	0.056	0.004	Yes
DMW25	Site 12	1/31/2022	<b>0.066</b>	0.024	NA	Yes
DMW26	Site 12		<b>0.072</b>	0.026	0.002	Yes
DMW27	Site 12		<b>0.075</b>	0.029	0.005	Yes

**Notes:**

bold = results above screening criteria

mg/m<sup>3</sup> = milligrams per cubic meter

NA = not applicable

<sup>1</sup> Maximum and average dust readings from daily PDR data downloads. Data are available upon request.



Date 1/3/2022

Logged by TR

Weather Slightly cloudy, hazy 45 - 55 °F

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated

[illegible]

[illegible]



Date 1/5/22

Project No. J310000800 SWDA Westside, Site 12, Treasure Island Page 1 of 1

Logged by Logan Schwing

Weather 49°F - 55°F. Cloudy AM some Fog

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated

[illegible]

[illegible]

[illegible]



[illegible]



Date 1 / 11 / 2022

Logged by     Tom    

Weather Sunny 49-57°F

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated, Zero cal in office

[illegible]



## AIR MONITORING LOG

Client Name NAVFAC

Date \_\_\_\_\_

1/12/22

Project / No. T.I. Westside Phase IV NTCRA / J310000800

Page 1 of 1

Logged by

TR

Weather 45-67°F

Smoggy-misty, Slightly Sunny

Instrument Type: Dust Trak II

Calibration Standards Used	Factory Calibrated

zero cal in office

[illegible]

## AIR MONITORING LOG

Client Name NAVFAC

Date \_\_\_\_\_

1/13/22

Project / No. T.I. Westside Phase IV NTCRA / J310000800



Page 1 of 1

Logged by

## Weather

Instrument Type: Dust Trak II

Calibration Standards Used    Factory Calibrated

Time	Dust Monitoring Station Number	Location	Instrument Reading (mg/m <sup>3</sup> )	Unit Number	Activities Remarks
0755	DmW19	upwind of import fill	0.121	1280	Before Import fill
↓	DmW20	downwind import fill	0.147	2341	
↓	DmW21	downwind import fill	0.121	2281	
0820	DmW19		0.079		zeroed in field still
↓	DmW20		0.084		high foggy conditions
↓	DmW21		0.085		
1300	DmW19		0.040		Import fill
↓	DmW20		0.047		
↓	DmW21		0.046		
1445	DmW19		0.027		Import fill
↓	DmW20		0.029		
↓	DmW21		0.032		
					
					
11/13/22					

[illegible]

255 11/17/22

## AIR MONITORING LOG

Client Name NAVFAC

Date \_\_\_\_\_

1/18/22

Project No. J310000800 SWDA Westside, Site 12, Treasure Island Page 1 of 1

Logged by Loren Schwing

Weather 55°F - 46°F. Partly cloudy.

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated

[illegible]



[illegible]

[illegible]



Client Name NAVFAC

Date \_\_\_\_\_

1 | 24 | 22

Project No. J310000800 SWDA Westside, Site 12, Treasure Island Page 1 of 1

Logged by Logan Schwinn

Weather 45°F-57°F. cloudy, thick AM fog/haze lingering through  
Instrument Type: Dust Trak II afternoon

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated

[illegible]



[illegible]

[illegible]

Time	Dust Monitoring Station Number	Location	Instrument Reading (mg/m <sup>3</sup> )	Unit Number	Activities, Remarks
0800	DMW22	DW Building Pad screening area	0.077	1280	thick fog low, above 100 ft, any work has
	DMW23	DW hauling box screened material to area	0.081	2341	Begin work.
	DMW24	DW area	0.081	2281	
1145	DMW22		0.067		no visible dust high,
	DMW23		0.065		thick haze high near
	DMW24		0.080		
1515	DMW22		0.020		readings have so to fog diss.
	DMW23		0.020		
	DMW24		0.021		

155 1/27/22

[illegible]



Date 1/31/22

Logged by Logan Schwing

Weather 45°F - 63°F Fog/Haze in AM

Instrument Type: Dust Trak II

Calibration Standards Used Factory Calibrated

[illegible]

**ATTACHMENT 2**  
**SUMMARY OF AIR MONITORING AND**  
**AIR SAMPLING RESULTS**  
**(Provided on CD)**

This page intentionally left blank

**Table 2-1: Ambient Pressure and Temperature Monitoring Results**

Sample Date	Ambient Pressure (inches of Hg)	Ambient Temperature (°F)	Ambient Temperature (°K)
1/25/2022	30.10	50.53	283.44
1/26/2022	30.09	48.58	282.36
1/27/2022	30.17	51.70	284.09
1/28/2022	30.25	53.40	285.04
1/28/2022	30.29	57.23	287.17

**Notes:**

Weather data collected from weather station at Building 572, Avenue M, Treasure Island, San Francisco, CA

°F = Degrees Fahrenheit

Hg = mercury

°K = Degrees Kelvin

Note: Air monitoring stations shutdown on days when import of clean soil was the only site activity



**Table 2-2: Particulate Matter Smaller than Ten Microns (PM10)**

Location ID	Sampling Period (Hours)	Sample Date	Particulate Matter Less Than 10 Microns in Diameter (ug/m <sup>3</sup> )	Delta between Downwind and Upwind Stations (ug/m <sup>3</sup> )	PM10 Exceedance? (Yes/No)
Screening Criteria					<b>50</b>
AMSW1	23.67	01/25/2022	27	NA	NA
	24.25	01/26/2022	19	NA	NA
	22.32	01/27/2022	36	NA	NA
	22.14	01/28/2022	23	NA	NA
	6.61	01/28/2022	32	NA	NA
AMSW2	9.88*	01/25/2022	38	11	No
	24.45	01/26/2022	25	6	No
	22.54	01/27/2022	42	6	No
	22.88	01/28/2022	28	5	No
	6.27	01/28/2022	38	6	No

**Notes:**

ug/m3 = micrograms per cubic meter

NA = Not applicable

PM10 = particulate matter less then 10 microns in diameter

\* = generator/sampler malfunction

**bold** = result above screening criteria

Note: Air monitoring stations shutdown on days when import of clean soil was the only site activity

**Table 2-3: Total Suspended Particulates Monitoring Results**

Location ID	Sampling Period (Hours)	Sample Date	Total Suspended Particulate (ug/m <sup>3</sup> )	Delta Between Downwind and Upwind Stations (ug/m <sup>3</sup> )	TSP Exceedance? (Yes/No)
Screening Criteria					50
AMSW1	23.70	01/25/2022	38.4325	NA	NA
	24.26	01/26/2022	29.6448	NA	NA
	22.32	01/27/2022	51.0853	NA	NA
	22.16	01/28/2022	36.7508	NA	NA
	6.59	01/28/2022	61.55	NA	NA
AMSW2	9.91*	01/25/2022	63.8339	25.4014	No
	24.46	01/26/2022	35.4306	5.7858	No
	22.55	01/27/2022	55.3399	4.2546	No
	22.9	01/28/2022	42.2495	5.4987	No
	6.32	01/28/2022	55.9483	-5.6017	No

**Notes:**

J = estimated value

ug/m<sup>3</sup> = micrograms per cubic meter

NA = Not applicable

TSP = total suspended particulate

**bold** = results above screening criteria

\* = generator/sampler malfunction

Note: Air monitoring stations shutdown on days when import of clean soil was the only site activity

**Table 2-4: Lead by EPA 6020 Monitoring Results**

Location ID	Sampling Period (Hours)	Sample Date	Lead (ug/m <sup>3</sup> )	Lead Exceedance? (Yes/No)
Screening Criteria				<b>1,575</b>
AMSW1	23.67	01/25/2022	0.0032	No
	24.25	01/26/2022	0.0026	No
	22.32	01/27/2022	0.0034	No
	22.14	01/28/2022	0.003	No
	6.61	01/28/2022	0.0051	No
AMSW2	9.88*	01/25/2022	0.0061	No
	24.45	01/26/2022	0.0027	No
	22.54	01/27/2022	0.0037	No
	22.88	01/28/2022	0.0041	No
	6.27	01/28/2022	0.0067	No

**Notes:**

J = indicates an estimated value

ug/m<sup>3</sup> = micrograms per cubic meter

\* = generator/sampler malfunction

**bold** = results above screening criteria

Note: Air monitoring stations shutdown on days when import of clean soil was the only site activity

Table 2-5: Polycyclic Aromatic Hydrocarbons by TO-13 Monitoring Results

Location ID	Sampling Period (Hours)	Sample Date	BAP(Eq) Exceed- ance? (Yes/No)	BAP(Eq)	2-Methyl- naph-thalene (ug/m³)	Acenaph- thene (ug/m³)	Acenaph- thylene (ug/m³)	Anthracene (ug/m³)	Benzo(a) anthracene (ug/m³)	Benzo(a) pyrene (ug/m³)	Benzo(b) fluoran- thene (ug/m³)	Benzo(g,h,i) perylene (ug/m³)	Benzo(k) fluoran- thene (ug/m³)	Chrysene (ug/m³)	Dibenz(a,h)anth- racene (ug/m³)	Fluoran- thene (ug/m3)	Fluorene (ug/m3)	Indeno (1,2,3- c,d) pyrene (ug/m3)	Naph- thalene (ug/m3)	Phenan- threne (ug/m3)	Pyrene (ug/m3)
Screening Criteria <sup>1</sup>				55,330	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE
AMSW1	24.27	01/26/2022	No	0	0.0036	0.00043 J	< 0.00053	< 0.00053	< 0.00053	< 0.00053	< 0.00053	< 0.00053	< 0.00053	< 0.00053	< 0.00053	0.00026 J	0.00044 J	< 0.00053	0.0086	0.0007	< 0.00053
	6.53	01/28/2022	No	0	0.0078	0.0011 J	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	< 0.0021	0.001 J	< 0.0021	0.018	0.0012 J	< 0.0021
AMSW2	24.45	01/26/2022	No	0	0.0032	0.00039 J	< 0.00047	0.00023 J	< 0.00047	< 0.00047	< 0.00047	< 0.00047	< 0.00047	< 0.00047	< 0.00047	0.00051	0.00061	< 0.00047	0.0074	0.0022	0.00034 J
	6.23	01/28/2022	No	0	0.0063	0.00085 J	< 0.002	< 0.002	< 0.002	< 0.002	< 0.002	< 0.002	< 0.002	< 0.002	< 0.002	0.00094 J	0.0013 J	< 0.002	0.015	0.0037	< 0.002

Notes:

<sup>1</sup> The dust action level was adjusted by a factor of 10 to account for the short-term duration of the project.

NA = Not applicable

NE = None established

BAP(Eq) = Benzo(a)pyrene equivalency

J = estimated value

ug/m³ = micrograms per cubic meter

**bold** = results above screening criteria

Note: Air monitoring stations shutdown on days when import of clean soil was the only site activity

**Table 2-6: Polychlorinated Biphenyls by TO-4A Monitoring Results**

Location ID	Sampling Period (Hours)	Sample Date	Total PCB Exceedance? (Yes/No)	Total PCB	PCB-1016 (Aroclor 1016) (ug/m <sup>3</sup> )	PCB-1221 (Aroclor 1221) (ug/m <sup>3</sup> )	PCB-1232 (Aroclor 1232) (ug/m <sup>3</sup> )	PCB-1242 (Aroclor 1242) (ug/m <sup>3</sup> )	PCB-1248 (Aroclor 1248) (ug/m <sup>3</sup> )	PCB-1254 (Aroclor 1254) (ug/m <sup>3</sup> )	PCB-1260 (Aroclor 1260) (ug/m <sup>3</sup> )
Screening Criteria				NE							
AMSW1	22.33	01/27/2022	NA	0	< 0.0008	< 0.0008	< 0.0008	< 0.0008	< 0.0008	< 0.0008	< 0.0008
AMSW2	22.55	01/27/2022	NA	0	< 0.00071	< 0.00071	< 0.00071	< 0.00071	< 0.00071	< 0.00071	< 0.00071

**Notes:**

NA = Not applicable

NE = None established

PCB = polychlorinated biphenyl

ug/m<sup>3</sup> = micrograms per cubic meter

< = nondetected less than associated reporting limit

J = estimated value

\* = sampler/generator malfunction

Note: Air monitoring station's shutdown on days when import of clean soil was the only site activity

**Table 2-7: Dioxin as 2,3,7,8-TCDD by TO-9A Monitoring Results**

Location ID	Sampling Period (Hours)	Sample Date	2,3,7,8-Tetrachlorodibenzo-p-dioxin (ug/m <sup>3</sup> )	Dioxin Exceedance? (Yes/No)
Screening Criteria				<b>10,000,000 ug/m<sup>3</sup></b>
AMSW1	23.71	01/25/2022	< 0.00000002	No
	22.16	01/28/2022	< 0.00000002	No
AMSW2	9.86*	01/25/2022	< 0.00000004	No
	22.86	01/28/2022	< 0.00000002	No

**Notes:**

J = estimated value

ug/m<sup>3</sup> = micrograms per cubic meter

< = nondetected less than associated reporting limit

**bold** = results above screening criteria

\* = generator / sampler malfunction

Note: Air monitoring station's shutdown on days when import of clean soil was the only site activity

**ATTACHMENT 3**  
**RADIOLOGICAL AIR MONITORING RESULTS**  
**(Provided on CD)**

This page intentionally left blank



Project Information								Effective as of: 17 Mar 2022			
Contract / Task Order Number:				Project Title / Location:				Gilbane Project Number:			
N62473-17-D-0005				IR Site 12 RD/RA, Treasure Island, SF, CA				J310000800			
Perimeter/Effluent Air Sampling Equipment						Breathing Zone Air Sampling Equipment					
Equip Number	Air Sampler Make/Model	Serial Number	Cal Due Date	Equip Number	Air Sampler Make/Model	Serial Number	Cal Due Date	Equip Number	Air Sampler Make/Model	Serial Number	Cal Due Date
PE01	LV-1	4532	5/20/21	BZ01				BZ01			
PE02	LV-1	4360	5/20/21	BZ02				BZ02			
PE03	LV-1	4352	4/20/22	BZ03				BZ03			
PE04	LV-1	4300	4/20/22	BZ04				BZ04			
PE05				BZ05				BZ05			
PE06				BZ06				BZ06			
PE07				BZ07				BZ07			
PE08				BZ08				BZ08			
PE09				BZ09				BZ09			
PE10				BZ10				BZ10			
PE11				BZ11				BZ11			
PE12				BZ12				BZ12			
PE13				BZ13				BZ13			
PE14				BZ14				BZ14			
PE15				BZ15				BZ15			
PE16				BZ16				BZ16			
PE17				BZ17				BZ17			
PE18				BZ18				BZ18			
PE19				BZ19				BZ19			
PE20				BZ20				BZ20			
Sample Counting Instruments											
Inst Number	Model Number	Serial Number	Cal Due Date	Count Time (min)		Background (cpm) <sup>a</sup>		Abs Ct Eff (cnts/dis) <sup>b</sup>		MDC (dpm/sample) <sup>c</sup>	
				Bkgrd	Source	Alpha	Beta	Alpha	Beta	Alpha	Beta
A	Protean	615068	9/15/21	1	1	0.0	1.1	0.352	0.355	15.4	29.0
B	Protean	9085100	10/5/21	1	1	0.0	1.2	0.356	0.352	15.2	29.9
C	Protean	9085100	10/1/22	1	1	0.0	1.2	0.359	0.355	15.1	29.6
D											
E											
Notes											
<sup>a</sup> background values obtained from instrument set-up worksheet <sup>b</sup> absolute counting efficiency = 4π efficiency calculated as ratio of measured count rate and contained activity [total dpm] of source (see IN-RP-141, <i>Alpha/Beta Scaler Instrument Set-Up and Operation</i> ) <sup>c</sup> MDC calculated using the Stapleton approximation (see IN-RP-141, <i>Alpha/Beta Scaler Instrument Set-Up and Operation</i> )											

**AIR SAMPLE RESULTS - PUBLIC EXPOSURE MONITORING**

Project Information										Effluent Air Concentration				Sampling Period				Color Codes							
Contract / Task Order Number: N62473-17-D-0005		Project Title / Location: IR Site 12 RD/IRA, Treasure Island, SF, CA				Gilbane Project Number: J310000800				Alpha		Beta		Air samples collected between 22 Mar 2021 and 31 Jan 2022				Value < MDC		Value < 0.1 x Effluent Conc					
										Radionuclide		Ra-226						Sr-90		< 72 hr decay time		Value > 0.1 x Effluent Conc			
										Information effective as of: 17 Mar 2022										Effluent Conc (µCi/ml)		9 E-13		6 E-12	
Sample Collection										Count Information				Sample Results				Initials							
Sample Number	Sample Type	Sample Location	Equip No	Ave Flow Rate (lpm)	Start Day Time	End Date Time	Elapsed Time (min)	Volume (ml)	Inst No	Count Date	Time (min)	Counting Units	Gross Activity		Net dpm		Activity (µCi/ml)		Effluent Conc (%)		Count Tech	Data Reviewer			
													Alpha	Beta	Alpha	Beta	Alpha	Beta	Alpha	Beta					
AS-0343	Perimeter	Upwind	PE03	60	1/24/22 7:45	1/24/22 15:20	455	2.7E+07	C	2/4/22	1	cpm	0.10	5.05	0.3	10.8	4.6E-15	1.8E-13	0.5%	3.0%	DB	CB			
AS-0344	Perimeter	Downwind	PE04	60	1/24/22 7:50	1/24/22 15:10	440	2.6E+07	C	2/4/22	1	cpm	0.30	5.65	0.8	12.5	1.4E-14	2.1E-13	1.6%	3.6%	DB	CB			
AS-0345	Perimeter	Upwind	PE03	60	1/25/22 6:10	1/25/22 15:20	550	3.3E+07	C	2/4/22	1	cpm	0.20	4.35	0.6	8.9	7.6E-15	1.2E-13	0.8%	2.0%	DB	CB			
AS-0346	Perimeter	Downwind	PE04	60	1/25/22 6:15	1/25/22 15:15	540	3.2E+07	C	2/4/22	1	cpm	0.05	4.25	0.1	8.6	1.9E-15	1.2E-13	0.2%	2.0%	DB	CB			
AS-0347	Perimeter	Upwind	PE03	60	1/26/22 6:10	1/26/22 15:25	555	3.3E+07	C	2/4/22	1	cpm	0.15	4.95	0.4	10.6	5.7E-15	1.4E-13	0.6%	2.4%	DB	CB			
AS-0348	Perimeter	Downwind	PE04	60	1/26/22 6:15	1/26/22 15:20	545	3.3E+07	C	2/4/22	1	cpm	0.25	4.40	0.7	9.0	9.6E-15	1.2E-13	1.1%	2.1%	DB	CB			
AS-0349	Perimeter	Upwind	PE03	60	1/27/22 6:35	1/27/22 15:20	525	3.2E+07	C	2/4/22	1	cpm	0.25	4.75	0.7	10.0	1.0E-14	1.4E-13	1.1%	2.4%	DB	CB			
AS-0350	Perimeter	Downwind	PE04	60	1/27/22 6:40	1/27/22 15:15	515	3.1E+07	C	2/4/22	1	cpm	0.25	5.20	0.7	11.3	1.0E-14	1.6E-13	1.1%	2.7%	DB	CB			
AS-0351	Perimeter	Upwind	PE03	60	1/28/22 6:15	1/28/22 15:10	535	3.2E+07	C	2/4/22	1	cpm	0.30	5.65	0.8	12.5	1.2E-14	1.8E-13	1.3%	2.9%	DB	CB			
AS-0352	Perimeter	Downwind	PE04	60	1/28/22 6:20	1/28/22 15:15	535	3.2E+07	C	2/4/22	1	cpm	0.25	5.55	0.7	12.3	9.8E-15	1.7E-13	1.1%	2.9%	DB	CB			
AS-0353	Perimeter	Upwind	PE03	60	1/31/22 6:15	1/31/22 15:05	530	3.2E+07	C	2/16/22	1	cpm	0.10	5.10	0.3	11.0	3.9E-15	1.6E-13	0.4%	2.6%	DB	CB			
AS-0354	Perimeter	Downwind	PE04	60	1/31/22 6:20	1/31/22 15:10	530	3.2E+07	C	2/16/22	1	cpm	0.35	4.60	1.0	9.6	1.4E-14	1.4E-13	1.5%	2.3%	DB	CB			
AS-0355	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0356	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0357	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0358	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0359	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0360	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0361	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0362	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0363	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0364	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0365	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0366	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0367	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0368	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0369	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0370	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0371	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0372	Perimeter	Downwind										cpm			#N/A	#N/A	#N/A	#N/A							
AS-0373	Perimeter	Upwind										cpm			#N/A	#N/A	#N/A	#N/A							

**CFM to LPM Converter**

1 cfm = 28.316846592 lpm	
Enter cfm:	2.1
lpm:	60.0

**Sample Types**

Perimeter
Effluent

**Counting Units**

cnts
cpm

10 CFR 20 Appendix B Table 2 Effluent Concentrations (listed in order of most to least restrictive radionuclide)

Column 1		
Alpha-Emitting Radionuclide	Retention Class	Air (µCi/ml)
Th-232	W	4 E-15
Pu-239/240	W	2 E-14
Am-241	W	2 E-14
U-233/234	Y	5 E-14
U-235	Y	6 E-14
U-238	Y	6 E-14
Ra-226	W	9 E-13
(TBD)	(TBD)	(TBD)

Column 1		
Beta-Emitting Radionuclide	Retention Class	Air (µCi/ml)
Sr-90	Y	6 E-12
Eu-152	W	3 E-11
Eu-154	W	3 E-11
Co-60	Y	5 E-11
Cs-137	D	2 E-10
(TBD)	(TBD)	(TBD)

Color Legend	
No exceedance above regulatory criteria	
Elevated however no exceedance above regulatory criteria	
Exceedance above regulatory criteria	

\* Effluent concentration is a regulatory number from the NRC considered protective of the public