


By: EKS\748 Date: 3/25/2024 1:35 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%_20240320



LEGEND

- (E) XXXXX

EXISTING
- (P) XXXXX

PROPOSED
- 2450

ELEVATION CONTOURS (FT)
- ---

EXISTING TOE OF BANK
- ---


EXISTING TOP OF BANK
- ---

NEW RETAINING WALL
- ---

LIMITS OF DISTURBANCE
- ---

OHW

ORDINARY HIGH WATER MARK
- RIPRAP REVETMENT
- SHORELINE ENHANCEMENT
- BEACH NOURISHMENT



| NO. | DESCRIPTION | DATE | DS. | DR. | NOTES | SIGNAGE | DATE | PROJECT INFORMATION | RIVER ENGINEERING |
|-----|--------------------------|---------|-----|-----|---|------------|---------|---|---------------------|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES | 1. HORIZONTAL PROJECTION: IPTM 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM | DS:GO,ES | 3-26-24 | BLACK SANDS RESORT BANK STABILIZATION PROJECT CONSTRUCTION PLAN SET OWYHEE COUNTY, IDAHO | IDAHO POWER COMPANY |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES | | DR:GO,ES | 3-26-24 | | WO NO: 27625213-01 |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES | | CH: JC | 3-26-24 | | OVERVIEW SHEET |
| | | | | | | SCALE: N/A | H V | | SHEET: 2 / 9 |
| | | | | | | | | | -- |



By: EKS\748 Date: 3/25/2024 1:36 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%.20240320

GENERAL PROJECT INFORMATION

PROJECT LAND OWNER: BUREAU OF LAND MANAGEMENT OPERATING UNDER A LEASE TO BLACK SANDS RESORT AND CAMPGROUND (BSRC) PROPERTY MANAGER

PROJECT LOCATION: PROJECT SITE IS LOCATED ON CJ STRIKE RESERVOIR SHORELINE APPROXIMATELY 1 MILE SOUTHEAST OF THE CJ STRIKE DAM.

ADDRESS
28114 BLACK SANDS RD
GRAND VIEW, IDAHO
83624

GPS COORDINATES
42° 56' 12.462" N
115° 57' 49.338" W

PROJECT CONSTRUCTION SCHEDULE:
PHASE 1 - FALL 2024 TO SPRING 2025
PHASE 2 - FALL 2025 TO SPRING 2026

UTILITIES
IN ACCORDANCE WITH SECTIONS 55-2201 - 55-2210, IDAHO CODE, THE CONTRACTOR MUST CONTACT DIGLINE STATEWIDE PHONE NUMBER 1-800-342-1585 NOT LESS THAN THREE WORKING DAYS PRIOR TO THE START OF ANY EXCAVATION FOR THIS PROJECT.

BSRC UTILITIES ARE KNOWN TO INCLUDE IRRIGATION, ELECTRICAL, WATER, AND WASTE WATER BUT OTHER UTILITIES MAY EXIST. CONTRACTOR SHALL CONTACT BSRC STAFF FOR A DESCRIPTION OF THE APPROXIMATE LOCATIONS. UNKNOWN UTILITIES MAY EXIST ONSITE. CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING LOCATION, PROTECTING AND RESTORING RESORT UTILITIES.

IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY IPC OF ANY CONFLICT WITH EXISTING UTILITIES.

ALL EXISTING FACILITIES, LANDSCAPE IMPROVEMENTS, UTILITIES AND VEGETATION NOT SPECIFICALLY IDENTIFIED FOR REMOVAL SHALL BE PROTECTED THROUGHOUT CONSTRUCTION OR RESTORED AT COMPLETION OF THE WORK.

SOIL
GENERALLY, SHORELINE SEDIMENT EXPOSURES ALONG THE BLACK SANDS RESORT INCLUDE FINE OUTWASH PLAIN AND TERRACE SOIL ALONG WITH LOESS DEPOSITS THAT MAKE UP A SANDY LOAM. USDA WEB SOIL SURVEY ([HTTPS://WEBSOILSURVEY.NRCS.USDA.GOV/APP/](https://websoilsurvey.nrcs.usda.gov/app/)) MAPPING OF THE PROJECT AREA IS LARGELY MADE UP OF TIMMERMAN SANDY LOAM ON THE WEST SHORE AND A COMBINATION OF HAWSLEY LOAMY SAND AND JACQUITH LOAMY FINE SAND ON THE SOUTH SHORE. THE LISTED TYPE OF SOILS CAN BE CONSTITUTED AS HIGHLY ERODIBLE SOILS SINCE THEY DEMONSTRATE THE CHARACTERISTICS OF SOILS SUSCEPTIBLE TO WATER EROSION. FURTHER FIELD INVESTIGATIONS DEMONSTRATE ACTIVE EROSION AND BANK MIGRATION RATES THAT BACK UP THE MAPPED SOIL CHARACTERISTICS.

EXISTING DATA

IN OCTOBER OF 2022, IPC STAFF COMPLETED A GPS AND DRONE SURVEY OF THE PROJECT SITE TO CAPTURE THE EXISTING SHORELINE EXTENTS, CAMPGROUND AMENITIES, AND ELEVATION INFORMATION. IN JUNE OF 2021, STAFF COMPLETED A BATHYMETRIC SURVEY OF THE SITE. STAFF COMBINED THE GPS SURVEY DATA, PHOTOGRAMMETRY COLLECTED BY THE DRONE, AND PREVIOUSLY COLLECTED BATHYMETRIC SURVEY INFORMATION TO DEVELOP A PROJECT SURFACE.

CONSTRUCTION MATERIALS

MATERIAL VOLUMES ARE APPROXIMATE ESTIMATES BASED ON IN-PLACE CONDITION DEFINED BY THE EXISTING GRADE, SUB-GRADE, AND FINAL GRADE.

ANY EXCESS MATERIALS SHALL BE STOCKPILED NEATLY WITHIN THE LIMITS OF DISTURBANCE. ALL MATERIALS DESIGNATED TO BE REMOVED. SHALL BE DISPOSED OF BY THE CONTRACTOR OFF SITE AT AN APPROVED DISPOSAL SITE PROVIDED BY THE CONTRACTOR.

CONSTRUCTION DEWATERING

CONTRACTOR SHALL PERFORM CONSTRUCTION DEWATERING IN COMPLIANCE WITH ALL APPLICABLE REGULATIONS AND PERMIT REQUIREMENTS.

VEHICLE OPERATIONS AND STAGING

VEHICLES AND WORK AREAS SHALL BE MAINTAINED IN A CLEAN STATE UTILIZING BEST MANAGEMENT PRACTICES INCLUDED IN THE IDAHO TRANSPORTATION DEPARTMENT'S "BEST MANAGEMENT PRACTICES MANUAL." TO COMPLY WITH ALL APPLICABLE RULES, REGULATIONS AND PERMIT REQUIREMENTS AT NO ADDITIONAL COST.

THE CONTRACTOR SHALL COMPLETE VEHICLE STAGING, CLEANING, MAINTENANCE, REFUELING, AND FUEL STORAGE IN VEHICLE STAGING AREA PLACED 100 FT OR MORE FROM THE RESERVOIR SHORELINE.

CONTRACTOR SHALL INSPECT ALL VEHICLES OPERATED WITHIN 100 FT OF ANY WATER BODY DAILY FOR FLUID LEAKS BEFORE LEAVING THE VEHICLE STAGING AREA. REPAIR ANY LEAKS DETECTED IN THE VEHICLE STAGING AREA BEFORE THE VEHICLE RESUMES OPERATION.

CONSTRUCTION ACCESS RESTORATION SHALL BE EQUAL TO OR BETTER THAN THE PRECONSTRUCTION CONDITION.

REGULATORY COMPLIANCE

ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL PERMIT CONDITIONS.

ANTICIPATED PERMITS INCLUDE, BUT NOT LIMITED TO, THE FOLLOWING:

- SECTION 404 CLEAN WATER ACT (USACE)
- SECTION 401 WATER QUALITY CERTIFICATION (IDEQ)
- STREAM CHANNEL ALTERATION

GENERAL NOTES

- ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM.
- CONTRACTOR AND IPC STAFF SHALL COMPLETE A PRECONSTRUCTION MEETING PRIOR TO BEGINNING CONSTRUCTION.
- CONTRACTOR SHALL HAVE AN APPROVED COPY OF ALL PROJECT PERMITS ONSITE AT ALL TIMES DURING CONSTRUCTION.
- CONTRACTOR SHALL NOTIFY IPC 14 DAYS PRIOR TO MOBILIZING MATERIALS OR EQUIPMENT ONSITE.
- CONTRACTOR SHALL FOLLOW ALL PERMIT REQUIREMENTS AND CONDITIONS.
- CROSS SECTIONS REPRESENT TYPICAL DIMENSIONS. ACTUAL DIMENSIONS MAY VARY.
- ALL CONSTRUCTION MATERIALS AND CONSTRUCTION WORK SHALL STAY WITHIN THE DEFINED AREA OF DISTURBANCE.
- MINIMIZE DISTURBANCE TO ADJACENT BSRC FACILITIES.
- TREES MAY BE TRIMMED AS NECESSARY TO COMPLETE THE WORK. ANY RESULTING WOODY DEBRIS SHALL BE PROPERLY DISPOSE OF OFFSITE.
- EROSION AND SEDIMENT CONTROL MEASURES DESIGN INFORMATION FOUND ON SHEET 4.
- IMPLEMENT AND MAINTAIN EROSION AND SEDIMENT CONTROL MEASURES IN ACCORDANCE ALL APPLICABLE REGULATORY REQUIREMENTS AND INDUSTRY BEST MANAGEMENT PRACTICES. EROSION/SEDIMENT CONTROL MEASURES SHALL BE INSTALLED BETWEEN ANY AREA OF EARTH DISTURBANCE AND THE WATER. EROSION AND SEDIMENT CONTROL MEASURES MUST BE MAINTAINED UNTIL CONSTRUCTION IS COMPLETED AND THE DISTURBED GROUND IS STABLE.
- ALL FUEL, OIL, AND OTHER HAZARDOUS MATERIALS SHALL BE STORED AND EQUIPMENT REFUELED AWAY FROM THE RESERVOIR TO ENSURE THAT A SPILL WILL NOT ENTER THE WATERWAY. EQUIPMENT MUST BE FREE OF FUEL AND LUBRICANT LEAKS.
- SHORELINE ENHANCEMENT REFERS TO ANY FILL MATERIAL PLACED ON THE LAND SIDE OF THE RETAINING WALL OR RIPRAP REVETMENT.
- BEACH NOURISHMENT REFERS TO ANY FILL MATERIAL PLACED ON THE RESERVOIR SIDE OF THE RETAINING WALL OR RIPRAP REVETMENT.

PLANTING GENERAL NOTES

TOTAL SEEDING AREA = 0.5 ACRES

LOCATION: TURF GRASS AREAS
ANY PRE-MIX FESCUE, TOLERANT OF HEAVY USE AND SUNNY AREAS--EXAMPLE: TALL FESCUE TURF BLEND FROM GREAT BASIN SEED (AT 8 LBS/1,000 FT²).

INSTRUCTIONS:

- SEED IN THE FALL (AFTER OCTOBER 15TH BUT PRIOR TO DEEP FREEZE) OR IN THE EARLY SPRING (MARCH TO EARLY APRIL).
- RAKE OR HARROW AREA PRIOR TO SEEDING. SOIL SHOULD NOT BE COMPACTED.
- BROADCAST SEED WITH A HAND-SEEDER OR INCORPORATE IN HYDRO-MULCH/SEED AS APPROPRIATE FOR SWPP REQUIREMENTS.
- UNLESS HYDROSEEDDED, RAKE OR HARROW AFTER SEEDING TO INCORPORATE SEEDS. DO NOT RAKE/HARROW IF AREA WAS HYDROSEEDDED.

LOCATION: FOR NON-IRRIGATED AREAS NEAR SHORELINE (NOT TURF GRASS AREAS)
SEE TABLE BELOW FOR SEED MIX

| SEED MIX | | |
|---|-----------|---------------|
| GRASS NAME | CULTIVAR* | LBS. PLS/ACRE |
| TALL WHEATGRASS (<i>THINOPYRUM PONTICUM</i>) | ALKAR | 5 |
| CRESTED WHEATGRASS (<i>AGROPYRON CRISTATUM</i>) | KIRK | 5 |
| RUSSIAN WILDRYE (<i>PSATHYROSTACHYS JUNCEA</i>) | BOZOISKY | 5 |
| WESTERN WHEATGRASS (<i>PASCOPYRUM SMITHII</i>) | ARRIBA | 5 |

| CONSTRUCTION MATERIAL QUANTITIES | | | |
|----------------------------------|----------|------|-----------------------------------|
| ITEM | QUANTITY | UNIT | NOTES |
| RIPRAP | 545 | CY | |
| BLOCK WALL BASE ROCK | 60 | CY | 1"- 2" MINUS WELL GRADED MATERIAL |
| FILTER ROCK | 260 | CY | |
| EXCAVATED MATERIAL | 3,211 | CY | |
| IMPORT FILL MATERIAL | 3,725 | CY | |
| FULL ULTRABLOCK (UB) | 252 | EA | |
| FULL FLAT CAP UB | 168 | EA | |
| RIGHT CORNER BENCH UB | 2 | EA | |
| LEFT CORNER BENCH UB | 2 | EA | |
| FULL CAP UB | 42 | EA | |
| FULL BENCH UB | 38 | EA | |


ABBREVIATIONS

| | | | |
|---------|---|-------|---|
| APPROX. | APPROXIMATELY | MIN | MINIMUM |
| BORR | BOTTOM OF RIPRAP | NTS | NOT TO SCALE |
| BORW | BOTTOM OF RETAINING WALL | OHW | ORDINARY HIGH WATERLINE |
| BSRC | BLACK SANDS RESORT AND CAMPGROUND | SF | SQUARE FEET |
| CFS | CUBIC FEET PER SECOND | SS | SOUTH SHORELINE |
| CP | CONTROL POINT | SWPPP | STORMWATER POLLUTION PREVENTION PLAN |
| CY | CUBIC YARDS | SY | SQUARE YARDS |
| EA | EROSIONAL AREA | TORR | TOP OF RIPRAP ELEVATION |
| ESC | EROSION AND SEDIMENT CONTROL | TORW | TOP OF RETAINING WALL ELEVATION |
| ELEV | ELEVATION | TESC | TEMPORARY EROSION AND SEDIMENT CONTROL |
| FT | FEET | UB | ULTRABLOCK |
| GPS | GLOBAL POSITIONING SYSTEM | USDA | UNITED STATES DEPARTMENT OF AGRICULTURE |
| IDEQ | IDAHO DEPARTMENT OF ENVIRONMENTAL QUALITY | USACE | UNITED STATES ARMY CORPS OF ENGINEERS |
| IN | INCHES | WET | EXISTING WETLAND |
| IPC | IDAHO POWER COMPANY | WS | WATER SURFACE |
| LBS | POUNDS | WSRR | WEST SHORELINE RIP RAP |
| LF | LINEAL FEET | WSRW | WEST SHORELINE RETAINING WALL |
| MAX | MAXIMUM | XS | CROSS SECTION |


| WETLAND PERMANENT IMPACT DISTURBANCE QUANTITIES | | | |
|---|------|------|-------|
| ITEM | AREA | UNIT | NOTES |
| WETLAND BELOW OHWM IMPACT AREA | 0.06 | AC | |
| WETLAND ABOVE OHWM IMPACT AREA | 0.30 | AC | |
| TOTAL IMPACTED WETLAND AREA | 0.36 | AC | |
| TOTAL WETLAND AREA | 0.48 | AC | |

| CONSTRUCTION LENGTHS | | |
|----------------------------------|-------------|-------|
| ITEM | LENGTH (LF) | NOTES |
| SOUTH SHORELINE RETAINING WALL | 485 | |
| SOUTH SHORELINE RIPRAP REVETMENT | 375 | |
| WEST SHORELINE RETAINING WALL | 565 | |
| WEST SHORELINE RIPRAP REVETMENT | 470 | |

| BANK GRADATION - PERCENT FINER | | |
|--------------------------------|-----------------------|----------------------------|
| PERCENT FINER | RIPRAP DIAMETER (IN.) | FILTER ROCK DIAMETER (IN.) |
| D100 | 20 | 4.00 |
| D85 | 18 | 2.50 |
| D50 | 14 | 1.50 |
| D15 | 6 | 0.10 |
| D5 | 4 | 0.08 |

| NO. | DESCRIPTION | DATE | DS. | DR. | NOTES | SIGNAGE | DATE | PROJECT INFORMATION | RIVER ENGINEERING |  An IDACORP Company |
|-----|--------------------------------|---------|-----|-----|---|----------|---------|--|---------------------|---|
| 1 | 30% PROJECT CONSTRUCTION PLANS | 6/15/23 | GO | ES | 1. HORIZONTAL PROJECTION: IPTM 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM | DS:GO,ES | 3-26-24 | BLACK SANDS RESORT BANK STABILIZATION PROJECT CONSTRUCTION PLAN SET OWYHEE COUNTY, IDAHO | IDAHO POWER COMPANY | |
| 2 | 60% PROJECT CONSTRUCTION PLANS | 12/1/23 | GO | ES | | DR:GO,ES | 3-26-24 | | WO NO: 27625213-01 | |
| 3 | 90% PROJECT CONSTRUCTION PLANS | 3/26/24 | GO | ES | | CH: JC | 3-26-24 | | NOTES SHEET | |
| | | | | | | SCALE: | N/A H | | SHEET: 3 / 9 | |
| | | | | | | | N/A V | | -- | |

By: EKS\748 Date: 3/25/2024 1:41 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%_20240320



LEGEND

- (E) XXXXX

EXISTING
- (P) XXXXX

PROPOSED
- 2450

ELEVATION CONTOURS (FT)
- ---

EXISTING TOE OF BANK
- ---

EXISTING TOP OF BANK
- ---



NEW RETAINING WALL
- ---

LIMITS OF DISTURBANCE
- RIPRAP REVETMENT
- SHORELINE ENHANCEMENT
- BEACH NOURISHMENT

NOTES:

1. ORDINARY HIGH WATER = 2457.9 FT
2. RIPRAP REVETMENT FINISHED GRADE OF SLOPE SHALL BE NO STEEPER THAN 3(H) : 1(V) SLOPE OTHER THAN BLENDING INTO EXISTING RESERVOIR BANKS AT EAST AND WEST TIE-IN LOCATIONS.
3. ANY LARGE BOULDERS OR VIABLE RIPRAP ENCOUNTERED DURING EXCAVATION SHALL BE SALVAGED FOR REUSE IN THE RIPRAP REVETMENT.
4. (E) = EXISTING, (P) = PROPOSED
5. SEED SHORELINE ENHANCEMENT AREA PER PLANTING NOTES ON NOTES SHEET
6. USE RIPRAP TO HELP TRANSITION GRADE AT THE RETAINING WALL AND RIPRAP REVETMENT TRANSITION LOCATIONS.
7. DESIGN PLAN RETAINING WALL HEIGHTS ARE APPROXIMATE.

| RIPRAP CONSTRUCTION LENGTHS | | | | |
|-----------------------------|----------------|-------------|--|--|
| BEGINNING STATION | ENDING STATION | LENGTH (LF) | APPROXIMATE RIPRAP REVETMENT HEIGHT (LF) | NOTES |
| -0+30 | 1+53 | 183 | 4.1 | |
| 4+28 | 5+50 | 122 | 4.1 AND 7.1 | RIPRAP HEIGHT TRANSITIONS FROM 4.1 FT AT STA. 4+27 TO 7.1 FT AT STA. 5+50. |
| 6+10 | 6+60 | 50 | 7.1 | |
| 8+10 | 8+30 | 20 | 6.0 | PLACE RIPRAP ON EXISTING SURFACE TO HELP TRANSITION BACK TO EXISTING GRADE |



| RETAINING WALL CONSTRUCTION LENGTHS | | | |
|-------------------------------------|----------------|-------------|------------------------------|
| BEGINNING STATION | ENDING STATION | LENGTH (LF) | APPROXIMATE WALL HEIGHT (LF) |
| 1+53 | 4+28 | 275 | 3.8 |
| 5+50 | 6+10 | 60 | 6.3 |
| 6+60 | 8+10 | 150 | 6.3 |

| CONSTRUCTION LENGTHS AND QUANTITIES | | | | | | | |
|-------------------------------------|-------------------|----------------------|--------------|-----------------------|----------------------------|---------------------------|---------------|
| ITEM | TOTAL LENGTH (LF) | VOLUME QUANTITY (CY) | # OF FULL UB | # OF FULL FLAT CAP UB | # OF RIGHT CORNER BENCH UB | # OF LEFT CORNER BENCH UB | # FULL CAP UB |
| RETAINING WALL | 485 | | 139 | 55 | 2 | 2 | 42 |
| BLOCK WALL BASE ROCK | 485 | 33 | | | | | |
| RIPRAP | 375 | 230 | | | | | |
| FILTER ROCK | 375 | 107 | | | | | |

| NO. | DESCRIPTION | DATE | DS. | DR. |
|-----|--------------------------|---------|-----|-----|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES |
| | | | | |
| | | | | |

| NOTES |
|---|
| 1. HORIZONTAL PROJECTION: IPTM |
| 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM |


| SIGNAGE | DATE |
|----------|---------|
| DS:GO,ES | 3-26-24 |
| DR:GO,ES | 3-26-24 |
| CH: JC | 3-26-24 |
| SCALE: | N/A H |
| | N/A V |

| PROJECT INFORMATION |
|---|
| BLACK SANDS RESORT BANK STABILIZATION PROJECT |
| CONSTRUCTION PLAN SET |
| OWYHEE COUNTY, IDAHO |


| RIVER ENGINEERING |
|---------------------|
| IDAHO POWER COMPANY |
| WO NO: 27625213-01 |
| SS PLAN & PROFILE |
| SHEET: 5 / 9 |




By: EKS/7/48 Date: 3/25/2024 1:43 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%_20240320




TYPICAL RETAINING WALL DETAIL FROM STATION 5+50 - 6+10
(NTS)




TYPICAL RETAINING WALL DETAIL FROM STATION 1+53 - 4+28
(NTS)




TYPICAL RIPRAP REVETMENT STEP DETAIL
(NTS)



TYPICAL RIPRAP REVETMENT DETAIL FROM STATION 6+10 - 6+60
(NTS)



TYPICAL RETAINING WALL FACE WITH 2 STACKED BLOCKS DETAIL
(NTS)




TYPICAL RETAINING WALL FACE WITH 3 STACKED BLOCKS AND BENCHDED BLOCKS DETAIL
(NTS)

| NO. | DESCRIPTION | DATE | DS. | DR. | NOTES | SIGNAGE | DATE | PROJECT INFORMATION | RIVER ENGINEERING |
|-----|--------------------------|---------|-----|-----|---|----------|----------------|--|---------------------|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES | 1. HORIZONTAL PROJECTION: IPTM 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM | DS:GO,ES | 3-26-24 | BLACK SANDS RESORT BANK STABILIZATION PROJECT CONSTRUCTION PLAN SET OWYHEE COUNTY, IDAHO | IDAHO POWER COMPANY |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES | | DR:GO,ES | 3-26-24 | | WO NO: 27625213-01 |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES | | CH: JC | 3-26-24 | | SS DETAILS |
| | | | | | | SCALE: | N/A H N/A V | | SHEET: 6 / 9 |



By: EKS/7/48 Date: 3/25/2024 1:45 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%_20240320



LEGEND

- (E) XXXXX

(P) XXXXX
- EXISTING

PROPOSED
- — — 2450 — — —

— — — — —

— — — — —

— — — — —

— — — — —

ELEVATION CONTOURS (FT)

EXISTING TOE OF BANK

EXISTING TOP OF BANK

NEW RETAINING WALL

LIMITS OF DISTURBANCE

RIPRAP REVETMENT

SHORELINE ENHANCEMENT

BEACH NOURISHMENT
- CONSTRUCTION LENGTHS AND QUANTITIES
- | ITEM | BEGINNING STATION | ENDING STATION | LENGTH (LF) | APPROXIMATE RIPRAP REVETMENT HEIGHT (LF) | VOLUME QUANTITY (CY) |
|-------------|-------------------|----------------|-------------|--|----------------------|
| RIPRAP | 10+00 | 14+40 | 440 | 5.1 | 285 |
| FILTER ROCK | 10+00 | 14+40 | 440 | | 135 |
- NOTES:
1. ORDINARY HIGH WATER = 2457.9 FT

2. RIPRAP REVETMENT FINISHED GRADE OF SLOPE SHALL BE NO STEEPER THAN 3(H) : 1(V) SLOPE OTHER THAN BLENDING INTO EXISTING RESERVOIR BANKS AT EAST AND WEST TIE-IN LOCATIONS.


3. SUITABLE RESERVOIR BED MATERIAL EXCAVATED FOR RIPRAP PLACEMENT SHALL BE REUSED ONSITE FOR SHORELINE ENHANCEMENT OR BEACH NOURISHMENT.

4. ANY LARGE BOULDERS OR VIABLE RIPRAP ENCOUNTERED DURING EXCAVATION SHALL BE SALVAGED FOR REUSE IN THE RIPRAP REVETMENT.

5. (E) = EXISTING, (P) = PROPOSED

6. SEED SHORELINE ENHANCEMENT AREA PER PLANTING NOTES ON NOTES SHEET.

7. USE RIPRAP TO HELP TRANSITION GRADE AT THE RETAINING WALL AND RIPRAP REVETMENT TRANSITION LOCATIONS.
- C.J. STRIKE RESERVOIR
-
- TYPICAL RIPRAP REVETMENT DETAIL
FROM STATION 10+00 - 14+40
(NTS)
-
-
- | NO. | DESCRIPTION | DATE | DS. | DR. |
|-----|--------------------------|---------|-----|-----|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES |
- | NOTES |
|---|
| 1. HORIZONTAL PROJECTION: IPTM |
| 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM |
- | SIGNAGE | DATE |
|----------|---------|
| DS:GO,ES | 3-26-24 |
| DR:GO,ES | 3-26-24 |
| CH: JC | 3-26-24 |
| SCALE: | N/A H |
| | N/A V |
- | PROJECT INFORMATION |
|---|
| BLACK SANDS RESORT BANK STABILIZATION PROJECT |
| CONSTRUCTION PLAN SET |
| OWYHEE COUNTY, IDAHO |
- | RIVER ENGINEERING |
|---------------------|
| IDAHO POWER COMPANY |
| WO NO: 27625213-01 |
| WSRR PLAN & PROFILE |
| SHEET: 7 / 9 |
-



(E) XXXXX EXISTING
(P) XXXXX PROPOSED

- — — — — 2450 — — — — — ELEVATION CONTOURS (FT)
- — — — — EXISTING TOE OF BANK
- — — — — EXISTING TOP OF BANK
- — — — — NEW RETAINING WALL
- — — — — LIMITS OF DISTURBANCE





SHORELINE ENHANCEMENT


 BEACH NOURISHMENT

1. ORDINARY HIGH WATER = 2457.9 FT
2. (E) = EXISTING, (P) = PROPOSED
3. SEED SHORELINE ENHANCEMENT AREA PER PLANTING NOTES ON NOTES SHEET
4. USE RIPRAP TO HELP TRANSITION GRADE AT THE RETAINING WALL AND RIPRAP REVETMENT TRANSITION LOCATIONS.
5. DESIGN PLAN RETAINING WALL HEIGHTS ARE APPROXIMATE.

| BEGINNING STATION | ENDING STATION | LENGTH (LF) | APPROXIMATE WALL HEIGHT (LF) | # OF FULL ULTRABLOCKS | # OF FULL FLAT CAP ULTRABLOCK |
|-------------------|----------------|-------------|------------------------------|-----------------------|-------------------------------|
| 14+40 | 20+05 | 565 | 3.8 | 113 | 113 |


| ITEM | VOLUME (CY) |
|---------------------------|-------------|
| BLOCK WALL BASE ROCK | 27 |
| ARMORED DRAIN RIP RAP | 12 |
| ARMORED DRAIN FILTER ROCK | 6 |
| RIPRAP BY BOAT RAMP | 20 |
| FILTER ROCK BY BOAT RAMP | 10 |




| NO. | DESCRIPTION | DATE | DS. | DR. | NOTES | SIGNAGE | DATE | PROJECT INFORMATION | RIVER ENGINEERING | |  An IDACORP Company |
|-----|--------------------------|---------|-----|-----|---|------------|---------|---|---------------------|----|---|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES | 1. HORIZONTAL PROJECTION: IPTM 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM | DS:GO,ES | 3-26-24 | BLACK SANDS RESORT BANK STABILIZATION PROJECT CONSTRUCTION PLAN SET OWYHEE COUNTY, IDAHO | IDAHO POWER COMPANY | | |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES | | DR:GO,ES | 3-26-24 | | WO NO: 27625213-01 | | |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES | | CH: JC | 3-26-24 | | WSRW PLAN & PROFILE | | |
| | | | | | | SCALE: N/A | H | | SHEET: 8 / 9 | | |
| | | | | | | | N/A | | V | -- | |



By: EKS:7/48 Date: 3/25/2024 1:49 PM Path: S:\Bankline Erosion\Projects\2022_CJ_BlackSands\05_Design\CAD\BlackSands_Design_90%_20240320



TYPICAL RETAINING WALL DETAIL FROM
STATION 14+40 - 20+05
(NTS)



PLAN VIEW
ARMORED DRAINAGE CHANNEL (NTS)

| NO. | DESCRIPTION | DATE | DS. | DR. | NOTES | SIGNAGE | DATE | PROJECT INFORMATION | RIVER ENGINEERING |
|-----|--------------------------|---------|-----|-----|---|----------|----------------|---|------------------------|
| 1 | 30% PROJECT DESIGN PLANS | 6/15/23 | GO | ES | 1. HORIZONTAL PROJECTION: IPTM 2. ALL ELEVATIONS ARE BASED ON THE NAVD88 DATUM | DS:GO,ES | 3-26-24 | BLACK SANDS RESORT BANK STABILIZATION PROJECT CONSTRUCTION PLAN SET OWYHEE COUNTY, IDAHO | IDAHO POWER COMPANY |
| 2 | 60% PROJECT DESIGN PLANS | 12/1/23 | GO | ES | | DR:GO,ES | 3-26-24 | | WO NO: 27625213-01 |
| 3 | 90% PROJECT DESIGN PLANS | 3/26/24 | GO | ES | | CH: JC | 3-26-24 | | WEST SHORELINE DETAILS |
| | | | | | | SCALE: | N/A H N/A V | | SHEET: 9 / 9 |

